



Supplier

Name Exel Composites Plc, Joensuu Factory

Address Muovilaaksontie 2
FI-82110 Heinävaara
Finland

Telephone +358-20 754 1200
Fax +358-20 754 1330

Product Description

Commercial Name Fiber reinforced plastic profiles

Chemical Name No chemical names for products

Constituent Parts Polyester resin, epoxy resin and/or vinylester, glassfiber, carbon fiber, additives

According to REACH (EY) N:o 1907/2006 fiber reinforced plastics materials are not considered as chemicals (Shape and mechanical performance are more important for the product than chemical composition) and for that reason they do not need to have MSDS. We (Exel Composites Plc.) want to share information and help our customers handling our products properly and this paper is for that purpose.

Physical and Chemical Properties (where appropriate)

Weight, dimensions Various to customer requirements, hollow and solid tubes and profiles

Colour, odour Colour acc. to customer requirements
Odour when products are over-heated

Boiling and melting points (°C) Na

Specific gravity at 15°C 1.60 – 2.00 g/cm³

Vapour pressure: vapour density

Solubility in water and organic solvents Negligible

Flash point and auto ignition temperature (°C) > 450°C

Flammability limits (% by volume)

Corrosive Qualities: pH value Solid

Percentage or volatiles Solid

Evaporation rate

Stability in air: conditions to avoid Stable

Hazardous combustion products Carbon monoxide, carbon dioxide

Incompatibility (materials to avoid) Not active material



Transport information

Proper shipping name

Glass/carbon fibre reinforced profiles

Uses

Whether for use as a solvent, and adhesive, for heat treatment, a paint, a lubricant, a cleaning agent/detergent, sterilising agent, a disinfectant or any other use.

Solid materials

Health Hazards

Results of any test regarding the toxicity of any substance in the product. The routes of exposure and any short term (acute) or long term (chronic) effects on health noted.

Not toxic in service temperatures
Skin irritation (dust)

Fire Hazards

Fire extinguishing media: special fire fighting procedures necessary; unusual fire/explosion hazards.

Water, foam, powder, CO₂

Spillage/Leakage Precautions

Measures necessary in the event of spillage/leakage: waste disposal method.

Solid material
Dust removing system when machined. Inert fully polymerised, Waste disposal in accordance with local requirements.

Handling Precautions

Protective clothing and type: respiratory protection: ventilation and other precautions

Eye protection when cutting/machining.
Dust mask complying with CEN P2
Long sleeved loose fitting clothing
Gloves and barrier cream recommended

Transport/Storage Precautions

Transport/storage temperature (°C)
Loading/unloading temperature (°C)

-50°C to +80°C
-50°C to +80°C

Health and First Aid Procedures

Procedures in the event of inhalation; ingestion; eye contact, skin contact, special precautions during treatment.

Dust: Medical aid in the event of irritation caused by inhalation and ingestion.
Eye contact: flushing with water
Skin contact: washing with soap and water

Legislation

Specific legislation relating to the use of the product should be given.



Local legislation relating to fire resistance, electrical insulation properties depending on use.

Please provide any additional information you consider relevant to this MSDS.