

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes Epoxy Filler 1500 basis
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
No further relevant information available.
- Application of the substance / the mixture
See our technical datasheet for application details of this product.
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
Suter Kunststoffe AG
Aefligenstrasse 3
3312 Fraubrunnen
Switzerland
Tel +41 (0)31 763 60 60
Fax +41 (0)31 763 60 61
email: info@swiss-composite.ch
- Further information obtainable from: environment protection department
- 1.4 Emergency telephone number:
ToxInfo Suisse, Tel.: 145
International: Tel. +41 (0)44 251 51 51

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.

- Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36/38: Irritating to eyes and skin.



Xi; Sensitising

R43: May cause sensitisation by skin contact.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- Information concerning particular hazards for human and environment:
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

Trade name: Epifanes Epoxy Filler 1500 basis

(Contd. of page 1)

- Classification system:
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS07



GHS09

- Signal word Warning
- Hazard-determining components of labelling:
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)
1,6-hexanediol diglycidyl ether
- Hazard statements
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements
P102 Keep out of reach of children.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information:
Contains epoxy constituents. May produce an allergic reaction.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterization: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.07.2014














Version number 3

Revision: 30.07.2014

Trade name: Epifanes Epoxy Filler 1500 basis

(Contd. of page 2)

• Dangerous components:

CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.: 01-2119491274-35	barium sulphate, natural substance with a Community workplace exposure limit	25-50%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)  Xi R36/38  Xi R43  N R51/53  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-25%
CAS: 9003-36-5 NLP: 500-033-5 Reg.nr.: 01-2119454392-40	reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)  Xi R36/38  Xi R43  N R51/53  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	2.5-10%
CAS: 16096-31-4 EINECS: 240-260-4 Reg.nr.: 01-2119463471-41	1,6-hexanediol diglycidyl ether  Xi R36/38  Xi R43 R52/53  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	2.5-10%

• Additional information:

For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
Use fire extinguishing methods suitable to surrounding conditions.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.07.2014

Version number 3

Revision: 30.07.2014

Trade name: Epifanes Epoxy Filler 1500 basis

(Contd. of page 3)

- 5.2 Special hazards arising from the substance or mixture
No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Not required.
- 6.2 Environmental precautions:
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire – and explosion protection:
No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: Not required.
Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities:
No further data; see item 7.
- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

Inhalative	Tijd gewogen gemiddelde over 8 uur / Exposure time	4 mg/m ³ (general population)
------------	--	---

7727-43-7 barium sulphate, natural

WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust
-----	---

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.07.2014

Version number 3

Revision: 30.07.2014

Trade name: Epifanes Epoxy Filler 1500 basis

(Contd. of page 4)

· **DNELs**

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Dermal	Acute - systemic effects, worker	8.3 mg/kg (Werker/Worker)
	Long-term - systemic effects, worker	8.3 mg/kg bw/day (Werker/Worker)
Inhalative	Acute-local effects, worker	12.3 mg/m ³ (Werker/Worker)
	Long-term - systemic effects, worker	12.3 mg/m ³ (Werker/Worker)

9003-36-5 reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)

Dermal	Acute-local effects, worker	8.3 --- (Werker/Worker)
	Long-term - systemic effects, worker	104.15 mg/kg bw/day (Werker/Worker)
Inhalative	Acute - systemic effects, worker	29.39 mg/kg (Werker/Worker)

· **PNECs**

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Aquatic compartent - freshwater	0.003 mg/L (Consument)
Aquatic compartment - marine water	0.0003 mg/L (4)
Aquatic compartment - sediment in freshwater	0.5 mg/kg sed dw (3)
Aquatic compartment - sediment in marine water	0.5 mg/kg sed dw (5)
Aquatic compartment - water, intermittent releases	0.013 mg/L (intermittent release water)
Sewage treatment plant	10 mg/L (7)
Terrestrial compartent - soil	0.05 mg/kg dw (8)

9003-36-5 reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)

Aquatic compartent - freshwater	0.003 mg/L (Consument)
Aquatic compartment - marine water	0.0003 mg/L (4)
Aquatic compartment - sediment in freshwater	0.294 mg/kg sed dw (3)
Aquatic compartment - sediment in marine water	0.0294 mg/kg sed dw (5)
Aquatic compartment - water, intermittent releases	0.013 mg/L (intermittent release water)
Sewage treatment plant	10 mg/L (7)
Terrestrial compartent - soil	0.05 mg/kg dw (8)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In

case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)

Trade name: Epifanes Epoxy Filler 1500 basis

(Contd. of page 5)

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Solid
Colour: According to product specification

- Odour: Characteristic

- Odour threshold: Not determined.

- pH-value: Not determined.

- Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: > 200 °C

- Flash point: 151 °C

- Flammability (solid, gaseous): Not applicable.

- Ignition temperature:

Decomposition temperature: Not determined.

- Self-igniting: Product is not selfigniting.

- Danger of explosion: Product does not present an explosion hazard.

- Explosion limits:

Lower: Not determined.

Upper: Not determined.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.07.2014

Version number 3

Revision: 30.07.2014

Trade name: Epifanes Epoxy Filler 1500 basis

(Contd. of page 6)

· Vapour pressure:	Not determined.
· Density at 20 °C:	1.508 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
VOC content:	VOC content:
Solids content:	100.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity:

- LD/LC50 values relevant for classification:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Oral	LD50	11400 mg/kg bw (rat)
------	------	----------------------

Dermal	LD50	>2000 mg/kg bw (rabbit)
--------	------	-------------------------

9003-36-5 reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)

Oral	LD50	11400 mg/kg bw (rat)
------	------	----------------------

Dermal	LD50	> 2000 mg/kg bw (rabbit)
--------	------	--------------------------

16096-31-4 1,6-hexanediol diglycidyl ether

Oral	LD50	2900 mg/kg bw (rat)
------	------	---------------------

Dermal	LD50	> 4900 mg/kg bw (rat)
--------	------	-----------------------

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.07.2014

Version number 3

Revision: 30.07.2014

Trade name: Epifanes Epoxy Filler 1500 basis

(Contd. of page 7)

- on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Oral	EC50	1.1 - 3.6 mg/l ((Daphnia magna))
Inhalative	LC50/96 h	1.5 - 7.7 mg/l ((Regenboogforel))

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxicological effects:
Remark: Toxic for fish
- Additional ecological information:
- General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.


- GB -


(Contd. on page 9)

Trade name: Epifanes Epoxy Filler 1500 basis

(Contd. of page 8)

SECTION 14: Transport information

- 14.1 UN-Number
• ADR, IMDG, IATA UN3082
- 14.2 UN proper shipping name
• ADR 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700))
• IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)), MARINE POLLUTANT
• IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700))
- 14.3 Transport hazard class(es)
• ADR


• Class 9 (M6) Miscellaneous dangerous substances and articles.
• Label 9
- IMDG, IATA


• Class 9 Miscellaneous dangerous substances and articles.
• Label 9
- 14.4 Packing group
• ADR, IMDG, IATA III
- 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
• Marine pollutant: Yes
Symbol (fish and tree)
• Special marking (ADR): Symbol (fish and tree)

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.07.2014

Version number 3

Revision: 30.07.2014

Trade name: Epifanes Epoxy Filler 1500 basis

(Contd. of page 9)

· Special marking (IATA):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
· Danger code (Kemler):	90
· EMS Number:	F-A, S-F
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.07.2014

Version number 3

Revision: 30.07.2014

Trade name: Epifanes Epoxy Filler 1500 basis

(Contd. of page 10)

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· * Data compared to the previous version altered.