



## RAKU® TOOL EL-2207-3 Resin

Revision date: 20.09.2021

EL-2207-3

Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

RAKU® TOOL EL-2207-3 Resin

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

model building material

##### Uses advised against

There are no data available on the mixture itself.

#### 1.3. Details of the supplier of the safety data sheet

Company name: Suter Kunststoffe AG  
Street: Aeßligenstrasse 3  
Place: CH-3312 Fraubrunnen  
Telephone: +41 (0)31 763 60 60  
e-mail: info@swiss-composite.ch

#### 1.4. Emergency telephone

##### number:

Tox Info Suisse

Emergency number: 145 - from abroad: + 41 44 251 51 51

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

bis-[4-(2,3-epoxipropoxy)phenyl]propane;

Bisphenol F-epichlorohydrin resin

##### Signal word:

Warning

##### Pictograms:



##### Hazard statements

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H319

Causes serious eye irritation.

H411

Toxic to aquatic life with long lasting effects.

##### Precautionary statements

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

P273

Avoid release to the environment.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352

IF ON SKIN: Wash with plenty of water.

P333+P313

If skin irritation or rash occurs: Get medical advice/attention.

P501

Dispose of contents/container to an appropriate recycling or disposal facility.


**RAKU® TOOL EL-2207-3 Resin**

Revision date: 20.09.2021

EL-2207-3

Page 2 of 10

**2.3. Other hazards**

None known

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Chemical characterization**

Mixture of the following substances with non-hazardous admixtures

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			25 - 50 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
9003-36-5	Bisphenol F-epichlorohydrin resin			5 - 15 %
	500-006-8		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1675-54-3	216-823-5	bis-[4-(2,3-epoxipropoxy)phenyl]propane	25 - 50 %
	dermal: LD50 = 23000 mg/kg; oral: LD50 = 11400 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100		
9003-36-5	500-006-8	Bisphenol F-epichlorohydrin resin	5 - 15 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg		

**Further Information**

none

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

Remove contaminated, saturated clothing immediately.  
 Remove affected person from the danger area and lay down.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours or decomposition products.  
 In case of respiratory tract irritation, consult a physician.

**After contact with skin**

Wash with plenty of water/soap.  
 If skin irritation or rash occurs: Get medical advice/attention.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

**After ingestion**

Rinse mouth immediately and drink plenty of water.  
 Never give anything by mouth to an unconscious person or a person with cramps.  
 Call a physician immediately.  
 Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

There are no data available on the mixture itself.

**4.3. Indication of any immediate medical attention and special treatment needed**

There are no data available on the mixture itself.



## RAKU® TOOL EL-2207-3 Resin

Revision date: 20.09.2021

EL-2207-3

Page 3 of 10

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### **Suitable extinguishing media**

Foam, Carbon dioxide (CO<sub>2</sub>), Dry extinguishing powder, Water spray jet

##### **Unsuitable extinguishing media**

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:

Carbon monoxide, Carbon dioxide

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### **General measures**

In case of vapour formation use respirator.

Provide adequate ventilation.

Wear personal protection equipment (refer to section 8).

Keep away from sources of ignition - No smoking.

#### 6.2. Environmental precautions

Clear contaminated areas thoroughly.

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

##### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Take up mechanically, placing in appropriate containers for disposal.

#### 6.4. Reference to other sections

none

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### **Advice on safe handling**

Keep container tightly closed.

Provide adequate ventilation.

Avoid contact with skin, eyes and clothes.

##### **Advice on protection against fire and explosion**

No special fire protection measures are necessary.

##### **Advice on general occupational hygiene**

Do not breathe vapour.

Wash hands before breaks and after work.

Do not eat, drink or smoke when using this product.

Avoid contact with skin, eyes and clothes.

Remove and wash contaminated clothes before re-use.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### **Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Protect from direct sunlight.

##### **Hints on joint storage**

Incompatible materials: Alkali (lye), Amines, Alcohols

##### **Further information on storage conditions**

Keep away from food, drink and animal feedingstuffs.


**RAKU® TOOL EL-2207-3 Resin**

Revision date: 20.09.2021

EL-2207-3

Page 4 of 10

Keep at temperatures between 5°C and 40°C.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection**
**8.1. Control parameters**
**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1317-65-3	Limestone, total inhalable	-	10		TWA (8 h)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			
Worker DNEL, long-term		inhalation	systemic	12,25 mg/m³
Worker DNEL, acute		inhalation	systemic	12,25 mg/m³
Worker DNEL, long-term		dermal	systemic	8,33 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	8,33 mg/kg bw/day
9003-36-5	Bisphenol F-epichlorohydrin resin			
Worker DNEL, long-term		dermal	systemic	104,15 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	29,39 mg/m³

**PNEC values**

CAS No	Substance	Value
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	
Freshwater		0,006 mg/l
Freshwater (intermittent releases)		0,018 mg/l
Marine water		0,0006 mg/l
Freshwater sediment		0,996 mg/kg
Marine sediment		0,0996 mg/kg
Secondary poisoning		11 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,196 mg/kg
9003-36-5	Bisphenol F-epichlorohydrin resin	
Freshwater		0,003 mg/l
Marine water		0,0003 mg/l
Freshwater sediment		0,294 mg/kg
Marine sediment		0,0294 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,237 mg/kg

**8.2. Exposure controls**
**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Tightly fitting goggles

## RAKU® TOOL EL-2207-3 Resin

Revision date: 20.09.2021

EL-2207-3

Page 5 of 10

### Hand protection

Chemical-resistant gloves (EN 374)

Suitable materials also for extended, direct contact (recommended: protection index 6, corresponding to a permeation rate > 480 minutes according to EN 374):

butyl rubber (Butyl) - = 0.7 mm thickness; i.e. < Butoject 898> made by KCL.

Nitrile rubber (Nitrile) - 0.4 mm thickness : i.e. < Camatril Velours 730> made by KCL.

Because of the great variety of glove types, the manufacturer's instructions for use must be adhered to.

The data given refer to information from glove manufacturers or have been assessed by analogy to similar materials. It should be taken into consideration, that due to the great number of influential factors such as the temperature, the daily durability of chemicals resistant protective gloves may be considerably reduced in practice, compared to the permeation rate assessed according to EN 374.

### Skin protection

Wear suitable protective clothing.

Safety Shoes

### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

If product is sprayed, use fresh-air breathing apparatus or (only short-term use) a combination filter A2-P2.

### Environmental exposure controls

There are no data available on the mixture itself.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	grey
Odour:	not determined

#### Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flash point:	> 150 °C

#### Flammability

Solid/liquid:	not determined
Gas:	not determined

#### Explosive properties

Product does not present an explosion hazard.

Auto-ignition temperature:	not determined
Decomposition temperature:	> 200 °C

#### Oxidizing properties

not applicable

pH-Value:	not determined
Viscosity / dynamic: (at 25 °C)	Paste
Water solubility: (at 20 °C)	Immiscible
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	1,02 g/cm³
Relative vapour density:	not determined

### 9.2. Other information

#### Other safety characteristics

Evaporation rate:	not determined
-------------------	----------------

#### Further Information


**RAKU® TOOL EL-2207-3 Resin**

Revision date: 20.09.2021

EL-2207-3

Page 6 of 10

There are no data available on the mixture itself.

**SECTION 10: Stability and reactivity**
**10.1. Reactivity**

Exothermic reaction with: Alkali (lye), Amines ,Alcohol

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.

**10.5. Incompatible materials**

Alkali (lye), Amines ,Alcohol

**10.6. Hazardous decomposition products**

The product is stable under storage at normal ambient temperatures.

**SECTION 11: Toxicological information**
**11.1. Information on hazard classes as defined in GB CLP Regulation**
**Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane				
	oral	LD50 11400 mg/kg	Rat		
	dermal	LD50 23000 mg/kg	Rat		
9003-36-5	Bisphenol F-epichlorohydrin resin				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

**Sensitising effects**

May cause an allergic skin reaction. (bis-[4-(2,3-epoxipropoxy)phenyl]propane; Bisphenol F-epichlorohydrin resin)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.


**RAKU® TOOL EL-2207-3 Resin**

Revision date: 20.09.2021

EL-2207-3

Page 7 of 10

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**
**Endocrine disrupting properties**

There are no data available on the mixture itself.

**Other information**

There are no data available on the mixture itself.

**SECTION 12: Ecological information**
**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane					
	Acute fish toxicity	LC50 2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 11 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 1,8 mg/l	48 h	Daphnia magna (Big water flea)		
9003-36-5	Bisphenol F-epichlorohydrin resin					
	Acute fish toxicity	LC50 mg/l 2,54	96 h	Fish		
	Acute algae toxicity	ErC50 mg/l > 1000	72 h	algae		
	Acute crustacea toxicity	EC50 mg/l 2,55	48 h	Daphnia magna (Big water flea)		

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
9003-36-5	Bisphenol F-epichlorohydrin resin			
	Biodegradable (OECD): 301 B	16 %	28	
	Poorly biodegradable.			

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	3,242
9003-36-5	Bisphenol F-epichlorohydrin resin	3,3

**BCF**

CAS No	Chemical name	BCF	Species	Source
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	31		

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

There are no data available on the mixture itself.

**12.7. Other adverse effects**

There are no data available on the mixture itself.

**RAKU® TOOL EL-2207-3 Resin**

Revision date: 20.09.2021

EL-2207-3

Page 8 of 10

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

It is not possible to give this product a waste code number according to the European waste catalogue because only the intended use of the user consents the assignment of a specific code number.

The waste code number must be agreed with the disposer / manufacturer / competent authority.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

Contaminated packages must be completely emptied and can be re-used following proper cleaning.

Packing which cannot be properly cleaned must be disposed of.

**SECTION 14: Transport information****Land transport (ADR/RID)****14.1. UN number:**

UN 3082

**14.2. UN proper shipping name:**ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Epoxide derivatives)**14.3. Transport hazard class(es):**

9

**14.4. Packing group:**

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

-

**Marine transport (IMDG)****14.1. UN number:**

UN 3082

**14.2. UN proper shipping name:**ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Epoxide derivatives)**14.3. Transport hazard class(es):**

9

**14.4. Packing group:**

III

Hazard label:

9



Marine pollutant:

yes

Special Provisions:

274, 335, 969

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-A, S-F

**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number:**

UN 3082

**14.2. UN proper shipping name:**ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Epoxide derivatives)**14.3. Transport hazard class(es):**

9



# Safety Data Sheet

according to UK REACH Regulation

## RAKU® TOOL EL-2207-3 Resin

EL-2207-3

Revision date: 20.09.2021

Page 9 of 10

### 14.4. Packing group:

Hazard label:

III

9



Special Provisions:

A97 A158 A197

Limited quantity Passenger:

30 kg G

Passenger LQ:

Y964

Excepted quantity:

E1

IATA-packing instructions - Passenger:

964

IATA-max. quantity - Passenger:

450 L

IATA-packing instructions - Cargo:

964

IATA-max. quantity - Cargo:

450 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

Yes



### 14.6. Special precautions for user

There are no data available on the mixture itself.

### 14.7. Maritime transport in bulk according to IMO instruments

There are no data available on the mixture itself.

### Other applicable information

There are no data available on the mixture itself.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

#### Additional information

This product does not contain substances of very high concern > 0,1% (Regulation (EC) No 1907/2006 (REACH), Article 57).

#### National regulatory information

Water hazard class (D):

2 - obviously hazardous to water

#### Additional information

"ZH 1/301 ""Data Sheet: Polyester and Epoxide resins (M 023)""

### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Bisphenol F-epichlorohydrin resin

## SECTION 16: Other information

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

### Relevant H and EUH statements (number and full text)

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

# Safety Data Sheet

according to UK REACH Regulation



**RAMPF®**  
discover the future

## RAKU® TOOL EL-2207-3 Resin

EL-2207-3

Revision date: 20.09.2021

Page 10 of 10

H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

### Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Key literature references and sources for data Regulation (EC) No 1907/2006; Regulation (EC) No. 1272/2008

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*