

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

SAFETY DATA SHEET

FOR INDUSTRIAL USE ONLY

EPIKURE (TM) Curing Agent MGS LH 160

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : EPIKURE (TM) Curing Agent MGS LH 160
SDS Number : 16S-00022
Product type : Curing Agent

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy Resin Systems

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier/Importer : Suter Kunststoffe AG
Aefligenstrasse 3
CH-3312 Fraubrunnen
Contact person : info@swiss-composite.ch
Telephone : General information
+41 (0)31 763 60 60

1.4 Emergency telephone number

Supplier : Tox Info Zurich
Telephone number : 145 (International +41 (0)44 251 51 51)

SECTION 2: Hazards identification


2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4 H302
Acute Tox. 4 H312
Skin Corr./Irrit. 1B H314
Eye Dam./Irrit. 1 H318
Skin Sens. 1 H317
Aquatic Chronic 3 H412

See Section 16 for the full text of the H statements declared above.

2.2 Label elements

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Harmful if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention	:	Wear protective gloves. Wear eye or face protection. Wear protective clothing. Avoid release to the environment.
Response	:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a POISON CENTER or physician. IF IN EYES: Immediately call a POISON CENTER or physician.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	m-phenylenebis(methylamine) 3-aminopropyltriethoxysilane 3-aminomethyl-3,5,5-trimethylcyclohexylamine
Supplemental label elements	:	Not applicable.

2.3 Other hazards

Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII	:	Not applicable.
Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	Not applicable.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Type
			Regulation (EC) No. 1272/2008 [CLP]	
3-aminomethyl-3,5,5-trimethylcyclohexylamine	EC:220-666-8 CAS : 2855-13-2 Index:612-067-00-9	>=50 - <75	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr./Irrit. 1B, H314 Eye Dam./Irrit. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
m-phenylenebis(methylamine)	RRN : 01-2119480150-50 EC:216-032-5 CAS : 1477-55-0 Index:	>=25 - <35	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr./Irrit. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
benzyl alcohol	RRN : 01-2119492630-38-XXXX EC:202-859-9 CAS : 100-51-6 Index:603-057-00-5	>=7 - <25	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Dam./Irrit. 2, H319	[1]
3-aminopropyltriethoxysilane	RRN : 01-2119480479-24 EC:213-048-4 CAS : 919-30-2 Index:612-108-00-0	>=0.1 - <1	Acute Tox. 4, H302 Skin Corr./Irrit. 1B, H314 Skin Sens. 1, H317	[1]
3-aminomethyl-3,5,5-trimethylcyclohexylamine	EC:220-666-8 CAS : 2855-13-2 Index:612-067-00-9	>=50 - <=75	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr./Irrit. 1B, H314 Eye Dam./Irrit. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
m-phenylenebis(methylamine)	RRN : 01-2119480150-50 EC:216-032-5 CAS : 1477-55-0 Index:	>=25 - <=50	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr./Irrit. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
benzyl alcohol	RRN : 01-2119492630-38-XXXX EC:202-859-9 CAS : 100-51-6 Index:603-057-00-5	>=10 - <=25	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Dam./Irrit. 2, H319	[1]
3-aminopropyltriethoxysilane	RRN : 01-2119480479-24 EC:213-048-4 CAS : 919-30-2 Index:612-108-00-0	>0 - <1	Acute Tox. 4, H302 Skin Corr./Irrit. 1B, H314 Skin Sens. 1, H317	[1]

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | | |
|--|---|---|
| Eye contact | : | Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. |
| Inhalation | : | Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | : | Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : | Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Protection of first aid personnel | : | No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact	:	Causes serious eye damage.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	:	Harmful if swallowed.

Over-exposure signs/symptoms

Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	:	Adverse symptoms may include the following: stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for	:	Fire-fighters should wear appropriate protective equipment and self-

fire-fighters

contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should

not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : Not available
Industrial sector specific solutions : Not available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNEL/DMEL Summary : Not available

PNEC Summary : Not available

8.2 Exposure controls

- Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Material: 730 Camatril
Minimum break through time: 480 min

Material: 898 Butoject

Minimum break through time: 480 min

Producer: This recommendation is valid only for our Product as delivered. If this product will be mixed with other substances you need to contact a supplier of CE approved protective gloves (e.g. KCL GmbH, D-36124 Eichenzell, Tel. 0049 (0) 6659 87300, Fax. 0049 (0) 6659 87155, email: vertrieb@kcl.de).

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers,

filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

General protective measures : Chemical splash goggles or face shield. Chemical-resistant gloves. Suitable protective footwear. Light protective clothing. Eyewash bottle with clean water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid
Color	: Blue.
Odor	: Amine-like.
Odor threshold	: Not available
pH	: Not available
Melting point/freezing point	: Not available
Initial boiling point and boiling range	: Greater than 200 °C
Flash point	: Greater than 100 °C
Evaporation rate	: Not available
Upper/lower flammability or explosive limits	: Lower: Not available Upper: Not available
Vapor pressure	: Not available
Vapor density	: Not available
Relative density	: Not available
Density	: Approx. 0.960 g/cm ³
Solubility(ies)	: Not available
Solubility in water	: insoluble
Partition coefficient: n-octanol/water	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity	: Dynamic: Approx. 10 - 50 mPa·s @ 25 °C (ISO 9371) Kinematic: Not available
Explosive properties	: Not available
Oxidizing properties	: Not available

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: Stable under normal conditions.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	LD50 Oral	Rat	1,030 mg/kg	-
m-phenylenebis(methylamine)				
	LD50 Oral	Rat	930 mg/kg	-
	LC50 Inhalation	Rat	3.89 mg/l	1 h
	LC50 Inhalation	Rat	2.4 mg/l	4 h
	LC50 Inhalation	Rat - Female	0.8 mg/l	4 h
	LD50 Dermal	Rabbit	2,000 mg/kg	-
benzyl alcohol				
	LD50 Oral	Rat	1,230 mg/kg	-
	LC50 Inhalation	Rat	> 4.178 mg/l	4 h
	LD50 Dermal	Rabbit	2,000 mg/kg	-
3-aminopropyltriethoxysilane				
	LD50 Oral	Rat	1,570 mg/kg	-
	LD50 Oral	Rat - Female	1,570 mg/kg	-
	LC50 Inhalation	Rat - Male		6 h
	LC50 Inhalation	Rat - Female		6 h
	LD50 Dermal	Rabbit	4,290 mg/kg	-
3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	LD50 Oral	Rat	1,030 mg/kg	-
m-phenylenebis(methylamine)				
	LD50 Oral	Rat	930 mg/kg	-
	LC50 Inhalation	Rat	3.89 mg/l	1 h
	LC50 Inhalation	Rat	2.4 mg/l	4 h
	LC50 Inhalation	Rat - Female	0.8 mg/l	4 h
	LD50 Dermal	Rabbit	2,000 mg/kg	-
benzyl alcohol				
	LD50 Oral	Rat	1,230 mg/kg	-
	LC50 Inhalation	Rat	> 4.178 mg/l	4 h
	LD50 Dermal	Rabbit	2,000 mg/kg	-
3-aminopropyltriethoxysilane				
	LD50 Oral	Rat	1,570 mg/kg	-
	LD50 Oral	Rat - Female	1,570 mg/kg	-

	LC50 Inhalation	Rat - Male		6 h
	LC50 Inhalation	Rat - Female		6 h
	LD50 Dermal	Rabbit	4,290 mg/kg	-

Conclusion/Summary : Not available

Acute toxicity estimates

Route	ATE value
Oral	1,023.9 mg/kg
Route	ATE value
Dermal	1,864.4 mg/kg
Route	ATE value
Inhalation (vapors)	36.67 mg/l
Route	ATE value
Inhalation (dusts and mists)	15 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
m-phenylenebis(methylamine)	Skin - Severe irritant	Rabbit		24 hrs	-
	eyes - Severe irritant	Rabbit		24 hrs	-
benzyl alcohol	Skin - Moderate irritant	Rabbit		24 hrs	-
3-aminopropyltriethoxysilane	eyes - Severe irritant	Rabbit		24 hrs	-
	Skin - Severe irritant	Rabbit		24 hrs	-
	eyes - Mild irritant	Rabbit			-
m-phenylenebis(methylamine)	Skin - Severe irritant	Rabbit		24 hrs	-
	eyes - Severe irritant	Rabbit		24 hrs	-
benzyl alcohol	Skin - Moderate irritant	Rabbit		24 hrs	-
3-aminopropyltriethoxysilane	eyes - Severe irritant	Rabbit		24 hrs	-
	Skin - Severe irritant	Rabbit		24 hrs	-
	eyes - Mild irritant	Rabbit			-

Conclusion/Summary

Skin : Not available
eyes : Not available

Respiratory : Not available

Sensitization

Product/ingredient name	Route of exposure	Species	Result
3-aminopropyltriethoxysilane	Skin	Guinea pig	Positive
	Skin	Guinea pig	Positive

Conclusion/Summary

Skin : Not available
Respiratory : Not available

Mutagenicity

Conclusion/Summary : Not available

Carcinogenicity

Conclusion/Summary : Not available

Reproductive toxicity

Conclusion/Summary : Not available

Teratogenicity

Conclusion/Summary : Not available

Specific target organ toxicity (single exposure)

Not available

Specific target organ toxicity (repeated exposure)

Not available

Aspiration hazard

Not available

Information on likely routes of exposure : Not available

Potential acute health effects

Eye contact : Causes serious eye damage.
Inhalation : No known significant effects or critical hazards.
Skin contact : Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion : Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain
watering
redness
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
Ingestion : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

Long term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

Potential chronic health effects

Conclusion/Summary : Not available

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
benzyl alcohol			
	Acute LC50 10,000 µg/l Fresh water	Fish - Bluegill	96 h
3-aminopropyltriethoxysilane			
	Acute LC50 > 934 mg/l - 203 Fish, Acute Toxicity Test	Fish - Zebra danio	96 h
	Acute EC50 331 mg/l - 202 Daphnia sp. Acute Immobilization Test and Reproduction Test	Aquatic invertebrates. Water flea	48 h
	Acute EC50 > 1,000 mg/l -	Aquatic plants - Algae	72 h
	Acute No-observable-effect-concentration 1.3 mg/l -	Aquatic plants - Algae	72 h
benzyl alcohol			
	Acute LC50 10,000 µg/l Fresh water	Fish - Bluegill	96 h
3-aminopropyltriethoxysilane			
	Acute LC50 > 934 mg/l - 203 Fish, Acute Toxicity Test	Fish - Zebra danio	96 h
	Acute EC50 331 mg/l - 202 Daphnia sp. Acute Immobilization Test and Reproduction Test	Aquatic invertebrates. Water flea	48 h
	Acute EC50 > 1,000 mg/l -	Aquatic plants - Algae	72 h
	Acute No-observable-effect-concentration 1.3 mg/l -	Aquatic plants - Algae	72 h

Conclusion/Summary : Not available

12.2 Persistence and degradability

Product/ingredient	Test	Result	Dose	Inoculum
--------------------	------	--------	------	----------

name				
3-aminopropyltriethoxysilane		-		
Remarks:	Not readily			
		-		
Remarks:	Not readily			

Conclusion/Summary : Not available

12.3 Bioaccumulative potential

Not available

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
m-phenylenebis(methylamine)	0.18	2.69	low
benzyl alcohol	1.1	-	low
3-aminopropyltriethoxysilane	1.7	3.40	low
m-phenylenebis(methylamine)	0.18	2.69	low
benzyl alcohol	1.1	-	low
3-aminopropyltriethoxysilane	1.7	3.40	low

12.4 Mobility in soil

Soil/water partition coefficient (KOC) : Not available

Mobility : Not available

12.5 Results of PBT and vPvB assessment

PBT : P: Not available
B: Not available
T: Not available

vPvB : vP: Not available
vB: Not available

12.6 Other adverse effects : No known significant effects or critical hazards.
No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

Packaging

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Regulatory information	14.1. UN number	14.2. UN proper shipping name	14.3. Transport hazard class(es)	14.4. Packing group
ADR/ADN	2735	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-Xylene-.a., .a.'-Diamine, Isophorone Diamine)	8	II
RID	2735	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-Xylene-.a., .a.'-Diamine, Isophorone Diamine)	8	II
ICAO/IATA	2735	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-Xylene-.a., .a.'-Diamine, Isophorone Diamine)	8	II
IMO/IMDG	2735	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-Xylene-.a., .a.'-Diamine, Isophorone Diamine)	8	II

14.5. Environmental hazards

Environmentally hazardous and/or Marine Pollutant : No.

- 14.6 Special precautions for user** : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Substances of very high concern

Carcinogen: Not listed

Mutagen: Not listed

Toxic to reproduction: Not listed

PBT: Not listed
vPvB: Not listed

Other EU regulations

REACH Status : The substance(s) in this product has (have) been Pre-Registered and/or Registered, or are exempted from registration, according to Regulation (EC) No. 1907/2006 (REACH).

Aerosol dispensers : Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

EU - Prior Informed Consent. List of chemicals subject to the international PIC procedure (Annex I - Part 1) : Not listed

EU - Prior Informed Consent. List of chemicals subject to the international PIC procedure (Annex I - Part 2) : Not listed

EU - Prior Informed Consent. List of chemicals subject to the international PIC procedure (Annex I - Part 3) : Not listed

AOX : Not available

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Hazardous incident ordinance : Not applicable.
Hazard class for water : WGK 2, Appendix No. 4
Technical instruction on air quality control : Number 5.2.5: 99.9 %

International regulations

International lists : Australia inventory (AICS) Not determined.
Canada inventory At least one component is not listed in DSL but all such components are listed in NDSL.
Japan inventory Not determined.
China inventory (IECSC) All components are listed or exempted.
Korea inventory All components are listed or exempted.
New Zealand Inventory (NZIoC) Not determined.
Philippines inventory (PICCS) All components are listed or exempted.
United States inventory (TSCA 8b) All components are listed or exempted.
Taiwan inventory (CSNN) All components are listed or exempted.

Chemical Weapons Convention : Not listed
List Schedule I Chemicals

Chemical Weapons Convention : Not listed
List Schedule II Chemicals : Not listed

Chemical Weapons Convention : Not listed
List Schedule III Chemicals : Not listed

: Not listed

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation
[Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
DMEL = Derived Minimal Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
PBT = Persistent, Bioaccumulative and Toxic
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302 (oral)	Calculation method
Acute Tox. 4, H312 (dermal)	Calculation method
Skin Corr./Irrit. 1B, H314	Calculation method
Eye Dam./Irrit. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements :

H302 (oral)	Harmful if swallowed.
H312 (dermal)	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332 (inhalation)	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.
H302 (oral)	Harmful if swallowed.
H312 (dermal)	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332 (inhalation)	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.

**Full text of classifications
[CLP/GHS]**

Acute Tox. 4, H302	ACUTE TOXICITY (oral) - Category 4
Acute Tox. 4, H312	ACUTE TOXICITY (dermal) - Category 4
Skin Corr./Irrit. 1B, H314	SKIN CORROSION/IRRITATION - Category 1B
Skin Sens. 1, H317	SKIN SENSITIZATION - Category 1
Eye Dam./Irrit. 1, H318	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Dam./Irrit. 2, H319	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4
Aquatic Chronic 3, H412	AQUATIC HAZARD (LONG-TERM) - Category 3
Acute Tox. 4, H302	ACUTE TOXICITY (oral) - Category 4
Acute Tox. 4, H312	ACUTE TOXICITY (dermal) - Category 4
Skin Corr./Irrit. 1B, H314	SKIN CORROSION/IRRITATION - Category 1B
Skin Sens. 1, H317	SKIN SENSITIZATION - Category 1
Eye Dam./Irrit. 1, H318	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Dam./Irrit. 2, H319	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4
Aquatic Chronic 3, H412	AQUATIC HAZARD (LONG-TERM) - Category 3

Date of printing : 03.08.2017
Date of issue/ Date of revision : 21.06.2017
Date of previous issue : 01.03.2017
Version : 6.0

Notice to reader

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. HEXION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION, except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.
 ® and (TM) Licensed trademarks of Hexion Inc.

This page left intentionally blank.