

according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI PUR

Revision date: 18.02.2021

Product code: 72XX

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

mibenco® FLÜSSIGGUMMI PUR

UFI:

NWF8-W026-K0EG-VDWE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Paint, Varnish.

Uses advised against

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Company name:	Suter Kunststoffe AG	
Street:	Aefligenstrasse 3	
Place:	CH - 3312 Fraubrunnen	
Telephone:	+41 (0)31 763 60 60	
e-mail:	info@swiss-composite.ch	
Internet:	www.swiss-composite.ch	
Responsible Department:	Sales - Team	
1.4. Emergency telephone	Tox Info Suisse Emergency number: 145	from abroad: +41 (0)44 251 51 51
number.		

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories: Flammable liquid: Flam. Liq. 2 Acute toxicity: Acute Tox. 4 Acute toxicity: Acute Tox. 4 Skin corrosion/irritation: Skin Irrit. 2 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Highly flammable liquid and vapour. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling xylene

Signal word:

Danger

Pictograms:

Dange



Hazard statements

H225 H312+H332 H315 Highly flammable liquid and vapour. Harmful in contact with skin or if inhaled. Causes skin irritation.



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI PUR

Revision date: 18.02.2021 Product code: 72XX Page 2 of 10 H411 Toxic to aquatic life with long lasting effects. **Precautionary statements** P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smokina. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P501 Dispose of waste according to applicable legislation.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification				
1330-20-7	xylene			55 - < 60 %	
	215-535-7	601-022-00-9			
	Flam. Liq. 3, Acute Tox	x. 4, Acute Tox. 4, Skin Irrit. 2; H226 H	332 H312 H315		
142-82-5	heptane; n-heptane			5 - < 10 %	
	205-563-8	601-008-00-2			
	Flam. Liq. 2, Skin Irrit. H315 H336 H304 H400	2, STOT SE 3, Asp. Tox. 1, Aquatic A) H410	cute 1, Aquatic Chronic 1; H225		

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	imits, M-factors and ATE	
1330-20-7	215-535-7	xylene	55 - < 60 %
	inhalation: ATE 1100 mg/kg	= 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE =	

Further Information

Full text of R-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Give nothing to eat or drink.

After inhalation

In case of inhaling spray mists, consult a doctor immediately and show him box or label. If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

After contact with skin

Remove contaminated, saturated clothing immediately. Change contaminated clothing. Wash thoroughly the body (shower or bath).



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI PUR

Revision date: 18.02.2021

Product code: 72XX

Page 3 of 10

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Foam. Dry extinguishing powder. Carbon dioxide (CO2). ABC powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Non-flammable. Burning produces heavy smoke. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Remove product from area of fire. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8.

6.2. Environmental precautions

Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Preventive measures: If handled uncovered, arrangements with local exhaust ventilation have to be used. It is recommended to design all work processes always so that the following is excluded: inhalation. skin contact. Eye contact. Take precautionary measures against static discharges.



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI PUR

Revision date: 18.02.2021

Product code: 72XX

Page 4 of 10

Advice on protection against fire and explosion

Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place. Take precautionary measures against static discharges.

Hints on joint storage

Materials to avoid: Acid. Base. Material, combustible. Oxidizing agents.

Further information on storage conditions

Keep away from sources of ignition - No smoking. Protect against: heat. Keep/Store only in original container.

7.3. Specific end use(s)

Paint, Varnish.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
142-82-5	n-Heptane	500	2085		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls



Appropriate engineering controls

Occupational exposure controls: Refer to chapter 7. No further action is necessary.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber). , Butyl rubber.

Revision No: 1,08



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI PUR

Revision date: 18.02.2021

Product code: 72XX

Page 5 of 10

Thickness of glove material: >0,4mm penetration time (maximum wearing period): >480min DIN-/EN-Norms: EN ISO 374

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation. insufficient absorbtion.

Environmental exposure controls

Refer to chapter 7 No further action is necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	liquid characteristic
Odour:	characteristic
Changes in the physical state Melting point/freezing point: Boiling point or initial boiling point and boiling range: Flash point:	not determined 98 °C -7 °C
Flammability Solid/liquid: Gas:	not applicable not applicable
Lower explosion limits: Upper explosion limits:	1 vol. % 8 vol. %
Auto-ignition temperature:	220 °C
Self-ignition temperature Solid: Gas:	not applicable not applicable
Decomposition temperature:	not determined
pH-Value:	not determined
Flow time: (at 20 °C)	> 40 (3 mm)
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	7 hPa
Density:	0,96 g/cm³
Relative vapour density:	not determined
9.2. Other information	
Other safety characteristics	
Solvent content:	70 %



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI PUR						
Revision date: 18.02.2021	Product code: 72XX	Page 6 of 10				
Solid content:	ca 30 %					
Evaporation rate:	not determined					
Further Information						

SECTION 10: Stability and reactivity

10.1. Reactivity

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.2. Chemical stability

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.3. Possibility of hazardous reactions

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.4. Conditions to avoid

Conditions to avoid: In case of warming: Danger of bursting container.

10.5. Incompatible materials

Alkalis (alkalis). Acid. Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Toxicological data are not available.

ATEmix calculated

ATE (dermal) 1913,0 mg/kg; ATE (inhalation vapour) 19,13 mg/l; ATE (inhalation aerosol) 2,609 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
1330-20-7	xylene					
	dermal	ATE mg/kg	1100			
	inhalation vapour	ATE	11 mg/l			
	inhalation aerosol	ATE	1,5 mg/l			

Irritation and corrosivity

Evaluation: Not an irritant.

STOT-repeated exposure

Has de-greasing effect on the skin.

Specific effects in experiment on an animal

Rat LD50: 4300 - 5800 mg/kg Acute toxicity, oral

Data apply to the main component.

Further information

Toxicological data are not available.

SECTION 12: Ecological information

12.1. Toxicity

Doesn't get into the sewage water as long as the process is carried out according to regulations. Very toxic for Water fleas.



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI PUR

Revision date: 18.02.2021

Product code: 72XX

Page 7 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose		[h] [d] Species	Source	Method
142-82-5	heptane; n-heptane					
	Acute fish toxicity	LC50	375 mg/l	96 h	GESTIS	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
142-82-5	heptane; n-heptane	4,66

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.7. Other adverse effects

No data available

Further information

Avoid release to the environment. Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Hand over to officially registered waste disposal company.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

14.2. UN proper shipping name:

Coating solution

UN 1139

Safety Data Sheet

according to UK REACH Regulation

Revision date: 18.02.2021	mibenco® FLÜSSIGGUMMI PUR Product code: 72XX	Page 8 of 10
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
Hazard label:	3	
Classification code:	F1	
Special Provisions:	640D	
Limited quantity:	5 L	
Excepted quantity:	E2	
Transport category:	2	
Hazard No: Tunnel restriction code:	30 D/E	
	D/E	
Inland waterways transport (ADN) <u>14.1. UN number:</u>	UN 1139	
14.2. UN proper shipping name:	Coating solution	
14.3. Transport hazard class(es):	3	
<u>14.4. Packing group:</u>	li	
Hazard label:	3	
Classification code: Special Provisions: Limited quantity: Excepted quantity: Marine transport (IMDG)	F1 640D 5 L E2	
<u>14.1. UN number:</u>	UN 1139	
14.2. UN proper shipping name:	Coating solution	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
Hazard label:	3	
Marine pollutant:	Yes	
Special Provisions:	-	
Limited quantity:	5 L	
Excepted quantity: EmS:	E2 F-E, S-E	
Air transport (ICAO-TI/IATA-DGR)	т-с, 3- с	
<u>14.1. UN number:</u>	UN 1139	
14.2. UN proper shipping name:	Coating solution	
14.3. Transport hazard class(es):	3	
14.4. Packing group: Hazard label:	II 3	

Safety Data Sheet

according to UK REACH Regulation

Revision date: 18.02.2021	mibenco® FLÜSSIGGUMMI PUI Product code: 72XX	R	Page 9 of 10		
	<u>.</u>				
	3				
Special Provisions:	A3				
Limited quantity Passenger: Passenger LQ:	1 L Y341				
Excepted quantity:	E2				
IATA-packing instructions - Passenger:	353				
IATA-max. quantity - Passenger:	5 L 364				
IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	60 L				
14.5. Environmental hazards					
ENVIRONMENTALLY HAZARDOUS:	Yes	NY.			
not applicable SECTION 15: Regulatory information					
15.1. Safety, health and environmental reg	ulations/legislation specific for the subs	stance or mixture			
EU regulatory information					
Restrictions on use (REACH, annex XVI	l):				
Entry 3					
2010/75/EU (VOC):	70 % (672 g/l)				
2004/42/EC (VOC): Additional information	70 % (672 g/l)				
VOC limit value: 840 g/l					
National regulatory information					
Water hazard class (D):	2 - obviously hazardous to water				
15.2. Chemical safety assessment					
Chemical safety assessments for sub	ostances in this mixture were not carried o	ut.			
SECTION 16: Other information					
Abbreviations and acronyms					
	ort des marchandises dangereuses par Ro e International Carriage of Dangerous Goo				

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI PUR

Revision date: 18.02.2021

Product code: 72XX

Page 10 of 10

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H312	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)