

according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

Revision date: 18.02.2021 Product code: 73XX Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

UFI: 50G8-D0RK-V0EY-JRGG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Paint, Varnish.

Uses advised against

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Company name: Suter Kunststoffe AG
Street: Aefligenstrasse 3
Place: CH - 3312 Fraubrunnen
Telephone: +41 (0)31 763 60 60
e-mail: info@swiss-composite.ch
Internet: www.swiss-composite.ch

Responsible Department: Sales - Team

1.4. Emergency telephone Tox Info Suisse Emergency number: 145 from abroad: +41 (0)44 251 51 51

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:

Flammable liquid: Flam. Liq. 2 Acute toxicity: Acute Tox. 4 Skin corrosion/irritation: Skin Irrit. 2

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Harmful if inhaled. Causes skin irritation.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

xylene

Signal word: Danger

Pictograms:







Hazard statements

H225 Highly flammable liquid and vapour.
H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H411 Toxic to aquatic life with long lasting effects.



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

Revision date: 18.02.2021 Product code: 73XX Page 2 of 11

Precautionary statements

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P501 Dispose of waste according to applicable legislation.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification				
1330-20-7	xylene				
	215-535-7	601-022-00-9			
	Flam. Liq. 3, Acute Tox. 4, Acut	H315			
142-82-5	heptane; n-heptane				
	205-563-8	601-008-00-2			
	Flam. Liq. 2, Skin Irrit. 2, STOT H315 H336 H304 H400 H410	uatic Chronic 1; H225			
100-41-4	ethylbenzene		1 - < 5 %		
	202-849-4	601-023-00-4			
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

opecine ou	iic. Ellillis, Wi-lac	tols and ATE	
CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	60 - < 65 %
	inhalation: ATE 1100 mg/kg	E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE =	
100-41-4	202-849-4	ethylbenzene	1 - < 5 %
		50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: mg/kg; oral: LD50 = 3500 mg/kg	

Further Information

Full text of R-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Give nothing to eat or drink.





according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

Revision date: 18.02.2021 Product code: 73XX Page 3 of 11

After inhalation

In case of inhaling spray mists, consult a doctor immediately and show him box or label. If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

After contact with skin

Remove contaminated, saturated clothing immediately. Change contaminated clothing. Wash thoroughly the body (shower or bath).

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Foam. Dry extinguishing powder. Carbon dioxide (CO2). ABC powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Non-flammable. Burning produces heavy smoke. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Remove product from area of fire. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8.

6.2. Environmental precautions

Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

Revision date: 18.02.2021 Product code: 73XX Page 4 of 11

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Preventive measures: If handled uncovered, arrangements with local exhaust ventilation have to be used. It is recommended to design all work processes always so that the following is excluded: inhalation. skin contact. Eye contact. Take precautionary measures against static discharges.

Advice on protection against fire and explosion

Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place. Take precautionary measures against static discharges.

Hints on joint storage

Materials to avoid: Acid. Base. Material, combustible. Oxidizing agents.

Further information on storage conditions

Keep away from sources of ignition - No smoking. Protect against: heat. Keep/Store only in original container.

7.3. Specific end use(s)

Paint, Varnish.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
142-82-5	n-Heptane	500	2085		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol		Post shift

8.2. Exposure controls



Appropriate engineering controls

Occupational exposure controls: Refer to chapter 7. No further action is necessary.



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

Revision date: 18.02.2021 Product code: 73XX Page 5 of 11

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber)., Butyl rubber.

Thickness of glove material: >0,4mm

penetration time (maximum wearing period): >480min

DIN-/EN-Norms: EN ISO 374

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation. insufficient absorbtion.

Environmental exposure controls

Refer to chapter 7 No further action is necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liauid Colour: characteristic Odour: characteristic

Changes in the physical state

Melting point/freezing point: not determined Boiling point or initial boiling point and 135 °C boiling range:

-7 °C Flash point:

Flammability

Solid/liquid: not applicable Gas: not applicable Lower explosion limits: 1 vol. % Upper explosion limits: 8 vol. % 430 °C Auto-ignition temperature:

Self-ignition temperature

Solid: not applicable Gas: not applicable not determined Decomposition temperature: pH-Value: not determined Flow time: > 40 (3 mm)(at 20 °C)

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.





according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

Revision date: 18.02.2021 Product code: 73XX Page 6 of 11

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined
Vapour pressure: 7 hPa

(at 20 °C)

Density: 0,9 g/cm³
Relative vapour density: not determined

9.2. Other information

Other safety characteristics

Solvent content: 70 % Solid content: ca 30 % Evaporation rate: not determined

Further Information

SECTION 10: Stability and reactivity

10.1. Reactivity

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.2. Chemical stability

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.3. Possibility of hazardous reactions

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.4. Conditions to avoid

Conditions to avoid:

In case of warming: Danger of bursting container.

10.5. Incompatible materials

Alkalis (alkalis). Acid. Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Toxicological data are not available.

ATEmix calculated

ATE (dermal) 1913,0 mg/kg; ATE (inhalation vapour) 19,13 mg/l; ATE (inhalation aerosol) 2,609 mg/l



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

Revision date: 18.02.2021 Product code: 73XX Page 7 of 11

CAS No	o Chemical name						
	Exposure route	Dose		Species	Source	Method	
1330-20-7	xylene						
	dermal	ATE mg/kg	1100				
	inhalation vapour	ATE	11 mg/l				
	inhalation aerosol	ATE	1,5 mg/l				
100-41-4	ethylbenzene						
	oral	LD50 mg/kg	3500	Rat	GESTIS		
	dermal	LD50 mg/kg	15400	Rabbit	GESTIS		
	inhalation (4 h) vapour	LC50	17,2 mg/l	Rat			
	inhalation aerosol	ATE	1,5 mg/l				

Irritation and corrosivity

Evaluation: Not an irritant.

STOT-repeated exposure

Has de-greasing effect on the skin.

Specific effects in experiment on an animal

Rat LD50: 4300 - 5800 mg/kg Acute toxicity, oral

Data apply to the main component.

Further information

Toxicological data are not available.

SECTION 12: Ecological information

12.1. Toxicity

Doesn't get into the sewage water as long as the process is carried out according to regulations. Very toxic for Water fleas.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Sourc	е	Method
142-82-5	heptane; n-heptane							
	Acute fish toxicity	LC50	375 mg/l	96 h		GEST	IS	
100-41-4	ethylbenzene							
_	Acute algae toxicity	ErC50	3,6 mg/l	96 h	Algen	GEST	IS	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
142-82-5	heptane; n-heptane	4,66
100-41-4	ethylbenzene	3,15

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

Revision date: 18.02.2021 Product code: 73XX Page 8 of 11

12.7. Other adverse effects

No data available

Further information

Avoid release to the environment. Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Hand over to officially registered waste disposal company.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1139

14.2. UN proper shipping name: Coating solution

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2
Transport category: 2
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1139

14.2. UN proper shipping name: Coating solution

14.3. Transport hazard class(es): 3



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

Revision date: 18.02.2021 Product code: 73XX Page 9 of 11

14.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1139

14.2. UN proper shipping name: Coating solution

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

E2

EmS:

F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1139

14.2. UN proper shipping name: Coating solution

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3

1 L

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



14.6. Special precautions for user

Warning: Combustible liquid.



according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

Revision date: 18.02.2021 Product code: 73XX Page 10 of 11

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC): 70 % (672 g/l) 2004/42/EC (VOC): 70 % (672 g/l)

Additional information

VOC limit value: 840 g/l

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation. H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.





according to UK REACH Regulation

mibenco® FLÜSSIGGUMMI SPRÜHFERTIG

Revision date: 18.02.2021 Product code: 73XX Page 11 of 11

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)