

according to UK REACH Regulation

## mibenco VERSIEGELUNG GLÄNZEND

Revision date: 18.02.2021 Product code: 00000228 Page 1 of 8

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

mibenco VERSIEGELUNG GLÄNZEND

UFI: AME8-90Q8-00E2-Y95F

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Further information: see technical data sheet.

### Uses advised against

Do not use for products which come into contact with the food stuffs.

# 1.3. Details of the supplier of the safety data sheet

Company name: Suter Kunststoffe AG
Street: Aefligenstrasse 3
Place: CH - 3312 Fraubrunnen
Telephone: +41 (0)31 763 60 60
e-mail: info@swiss-composite.ch
Internet: www.swiss-composite.ch

Responsible Department: Sales - Team

1.4. Emergency telephone Tox Info Suisse Emergency number: 145 from abroad: +41 (0)44 251 51 51

number:

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

# **GB CLP Regulation**

Hazard categories:

Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

May cause an allergic skin reaction.

# 2.2. Label elements

# **GB CLP Regulation**

# Hazard components for labelling

Fettalkoholpolyglykolether Isotridecylalcohol, ethoxylated decyl D-glucoside

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one

Signal word: Warning

Pictograms:



# **Hazard statements**

H317 May cause an allergic skin reaction.

### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing



according to UK REACH Regulation

## mibenco VERSIEGELUNG GLÄNZEND

Revision date: 18.02.2021 Product code: 00000228 Page 2 of 8

protection.

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P501 Dispose of waste according to applicable legislation.

### Special labelling of certain mixtures

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, 2-Methyl-3(2H)

-isothiazolone. May produce an allergic reaction.

# 2.3. Other hazards

No information available.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### **Hazardous components**

CAS No	Chemical name			
	EC No	Index No	REACH No	
	GHS Classification			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
2372-82-9	N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine			< 1 %
	219-145-8			
	Acute Tox. 4, Skin Corr. 1A, Aquati	c Acute 1, Aquatic Chronic 1; H302 H	H314 H400 H410	
2682-20-4	2-Methyl-3(2H)-isothiazolone			< 1 %
	220-239-6			
	Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1; H311 H301 H314 H317			
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			
	220-120-9	613-088-00-6		
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1; H302 H315 H318 H317 H400			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

opositio ostro: Elittio, ili tuotoro una ATE				
CAS No	EC No	Chemical name	Quantity	
	Specific Conc.	Limits, M-factors and ATE		
2372-82-9	219-145-8	N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine	< 1 %	
	oral: ATE = 50	oral: ATE = 500 mg/kg		
2682-20-4	220-239-6	2-Methyl-3(2H)-isothiazolone	< 1 %	
	dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg			
2634-33-5	220-120-9	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	< 1 %	
	oral: ATE = 50	0 mg/kg Skin Sens. 1; H317: >= 0,05 - 100		

# Labelling for contents according to Regulation (EC) No 648/2004

< 5 % anionic surfactants, preservation agents (Benzisothiazolinone).

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

# **General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Give nothing to eat or drink.





according to UK REACH Regulation

## mibenco VERSIEGELUNG GLÄNZEND

Revision date: 18.02.2021 Product code: 00000228 Page 3 of 8

### After inhalation

In case of inhaling spray mists, consult a doctor immediately and show him box or label. If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

#### After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. Remove contaminated, saturated clothing immediately. Change contaminated clothing. Wash thoroughly the body (shower or bath).

#### After contact with eves

Rinse immediately carefully and thoroughly with eye-bath or water. If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

# 4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

## Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Foam. Dry extinguishing powder. Carbon dioxide (CO2). ABC powder.

### Unsuitable extinguishing media

High power water jet.

## 5.2. Special hazards arising from the substance or mixture

Non-flammable. Burning produces heavy smoke. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Co-ordinate fire-fighting measures to the fire surroundings. The product itself does not burn.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

### **General measures**

Provide adequate ventilation. See protective measures under point 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

### Other information

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Treat the recovered material as prescribed in the section on waste disposal.

# 6.4. Reference to other sections

See protective measures under point 7 and 8.



according to UK REACH Regulation

## mibenco VERSIEGELUNG GLÄNZEND

Revision date: 18.02.2021 Product code: 00000228 Page 4 of 8

### **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

### Advice on safe handling

No special precautionary measures are necessary.

### Advice on protection against fire and explosion

No special precautionary measures are necessary.

### Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place.

## Hints on joint storage

Materials to avoid: Acid. Base. Material, combustible. Oxidizing agents.

## Further information on storage conditions

Protect against direct sunlight.

### 7.3. Specific end use(s)

Further information: see technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

# Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

### 8.2. Exposure controls



## Appropriate engineering controls

Occupational exposure controls: Refer to chapter 7. No further action is necessary.

## Individual protection measures, such as personal protective equipment

## Eye/face protection

Wear eye protection/face protection. Suitable eye protection: Framed glasses. Goggles.

# **Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber). German Industry Norms (DIN) / European Norms (EN): EN ISO 374 Breakthrough times and swelling properties of the material must be taken into consideration.



according to UK REACH Regulation

## mibenco VERSIEGELUNG GLÄNZEND

Revision date: 18.02.2021 Product code: 00000228 Page 5 of 8

### Skin protection

Wear suitable protective clothing. Suitable protective clothing: Lab apron.

Protect skin by using skin protective cream.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation. insufficient absorbtion.

# **Environmental exposure controls**

Refer to chapter 7 No further action is necessary.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: cloudy
Odour: characteristic

### Changes in the physical state

Melting point/freezing point: 0 °C
Boiling point or initial boiling point and 100 °C
boiling range:

Flash point: 200 °C

**Flammability** 

Solid/liquid: not applicable
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties** 

Not oxidising.

pH-Value (at 20 °C): 7,5

Water solubility: completely miscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density:

Relative vapour density:

not determined

not determined

not determined

not determined

not determined

## 9.2. Other information

Other safety characteristics

Solvent content: 5 %
Solid content: not determined
Evaporation rate: not determined

**Further Information** 

## **SECTION 10: Stability and reactivity**



according to UK REACH Regulation

## mibenco VERSIEGELUNG GLÄNZEND

Revision date: 18.02.2021 Product code: 00000228 Page 6 of 8

### 10.1. Reactivity

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

### 10.2. Chemical stability

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

### 10.3. Possibility of hazardous reactions

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

### 10.4. Conditions to avoid

Conditions to avoid:

In case of warming: Danger of bursting container.

### 10.5. Incompatible materials

Alkalis (alkalis). Acid. Oxidizing agents.

## 10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

### Acute toxicity

Toxicological data are not available.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2372-82-9	N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine				
	oral	ATE 500 mg/kg			
2682-20-4	2-Methyl-3(2H)-isothiazolone				
	oral	ATE 100 mg/kg			
	dermal	ATE 300 mg/kg			
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one				
	oral	ATE 500 mg/kg			

### **Further information**

Toxicological data are not available.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

No data available

# 12.2. Persistence and degradability

No data available

# 12.3. Bioaccumulative potential

No data available

### 12.4. Mobility in soil

No data available

# 12.5. Results of PBT and vPvB assessment

No data available





according to UK REACH Regulation

## mibenco VERSIEGELUNG GLÄNZEND

Revision date: 18.02.2021 Product code: 00000228 Page 7 of 8

#### 12.7. Other adverse effects

According to the criteria of the EC-classification and labelling "dangerous for the environment" (93/21/EEC) the material/product is not to be classified as dangerous to the environment.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

# **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

### List of Wastes Code - residues/unused products

other than those mentioned in 08 01 11

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

# List of Wastes Code - used product

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

### List of Wastes Code - contaminated packaging

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

# Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Hand over to officially registered waste disposal company.

# **SECTION 14: Transport information**

## 14.6. Special precautions for user

No information available.

## 14.7. Maritime transport in bulk according to IMO instruments

not applicable

# Other applicable information

Not a hazardous material with respect to transportation regulations.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

### **Additional information**

Regulation (EC) No. 648/2004 (Detergents regulation).

## **National regulatory information**



according to UK REACH Regulation

## mibenco VERSIEGELUNG GLÄNZEND

Revision date: 18.02.2021 Product code: 00000228 Page 8 of 8

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

# Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method

### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, 2-Methyl-3(2H) -isothiazolone. May produce an allergic reaction.

### **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The product is classified and labelled according to EC directives or corresponding national laws.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)