# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name : SD 8605
Product code : 786.
HARDENER
UFI : Y5S5-F0HR-2007-PF56

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Hardener
Uses advised against : data not available

### 1.3. Details of the supplier of the safety data sheet

Registered company name : Suter Kunststoffe AG

Address : Aefligenstrasse 3, CH-3312 Fraubrunnen

Telephone : +41 (0)31 763 60 60 Fax : +41 (0)31 763 60 61 .e-mail: info@swiss-composite.ch

Site web : https://www.swiss-composite.ch

### 1.4. Emergency telephone number : .

Association/Organisation : ToxInfo Zürich, Telefon 145 (International +41 44 251 51 51)

## SECTION 2 : HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Skin corrosion, Category 1B (Skin Corr. 1B, H314).
Serious eye damage, Category 1 (Eye Dam. 1, H318).
Skin sensitisation, Category 1 (Skin Sens. 1, H317).
Reproductive toxicity, Category 1B (Repr. 1B, H360Fd).
Hazardous to the aquatic environment - Chronic hazard, Category 1 (Aquatic Chronic 1, H410).
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

### 2.2. Label elements

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :

GHS05 GHS07 GHS08 GHS09

Signal Word :
DANGER
Product identifiers :

| | |
|---|---|
| EC 618-561-0 | REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA |
| EC 268-626-9 | POLYETHYLENEPOLYAMINES |
| EC 201-245-8 | BISPHENOL A |
| EC 223-775-9 | 3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE |

| | |
|---|---|
| EC 200-712-3 | SALICYLIC ACID |
| Additional labeling : | |
| | For professional use only. |
| Hazard statements : | |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H360Fd | May damage fertility. Suspected of damaging the unborn child. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| Precautionary statements - Prevention : | |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P264 | Wash hands thoroughly after handling. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/ ... |
| Precautionary statements - Response : | |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTER/doctor/... |
| P362 + P364 | Take off contaminated clothing and wash it before reuse. |
| Other information : | |

### 2.3. Other hazards

The mixture contains substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table
The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

**Composition :**

| Identification | (EC) 1272/2008 | Note | % |
|---|---|---|---|
| CAS: 9046-10-0<br>EC: 618-561-0<br>REACH: 01-2119557899-12-XXXX<br><br>REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA | GHS05<br>Dgr<br>Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Aquatic Chronic 3, H412 | | 25 <= x % < 50 |
| CAS: 68131-73-7<br>EC: 268-626-9<br>REACH: 01-2119485823-28-XXXX<br><br>POLYETHYLENEPOLYAMINES | GHS07, GHS05, GHS09<br>Dgr<br>Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Skin Corr. 1B, H314<br>Skin Sens. 1, H317<br>Eye Dam. 1, H318<br>Aquatic Acute 1, H400<br>M Acute = 1<br>Aquatic Chronic 1, H410<br>M Chronic = 1 | | 25 <= x % < 50 |
| CAS: 80-05-7<br>EC: 201-245-8<br>REACH: 01-2119457856-23-XXXX<br><br>BISPHENOL A | GHS05, GHS09, GHS07, GHS08<br>Dgr<br>Skin Sens. 1, H317<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>Repr. 1B, H360F<br>Aquatic Chronic 2, H411 | [1]<br>[2]<br>[6] | 10 <= x % < 25 |
| CAS: 4067-16-7<br>EC: 223-775-9<br>REACH: 01-219485826-22-XXXX | GHS07, GHS05, GHS09<br>Dgr<br>Acute Tox. 4, H302<br>Acute Tox. 4, H312 | | 2.5 <= x % < 10 |

| | | | |
|---|---|---|---|
| 3,6,9,12-TETRA-AZATETRADECAMETH YLENEDIAMINE | Skin Corr. 1B, H314<br>Skin Sens. 1, H317<br>Eye Dam. 1, H318<br>Aquatic Acute 1, H400<br>M Acute = 1<br>Aquatic Chronic 1, H410<br>M Chronic = 1 | | |
| CAS: 100-51-6<br>EC: 202-859-9<br>REACH: 01-2119492630-38-XXXX<br><br>BENZYL ALCOHOL | GHS07<br>Wng<br>Acute Tox. 4, H302<br>Eye Irrit. 2, H319<br>Acute Tox. 4, H332 | [1] | 2.5 <= x % < 10 |
| CAS: 69-72-7<br>EC: 200-712-3<br>REACH: 01-2119486984-17-XXXX<br><br>SALICYLIC ACID | GHS07, GHS05, GHS08<br>Dgr<br>Acute Tox. 4, H302<br>Eye Dam. 1, H318<br>Repr. 2, H361d | [2] | 2.5 <= x % < 10 |

(Full text of H-phrases: see section 16)

**Information on ingredients :**

[1] Substance for which maximum workplace exposure limits are available.
[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.
[6] Substances of very high concern (SVHC).

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

### 4.1. Description of first aid measures

**In the event of exposure by inhalation :**

If inhaled, move the patient to fresh air and keep warm and rest.
Never give anything by mouth. If unconscious, place in recovery position and call an ambulance.

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.
Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.
Flush with large amounts of water. Remove contact lenses if the victim is. Continue to rinse. Seek medical attention if symptoms persist.

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.
Remove any soiled or splashed clothing immediately.
Watch out for any remaining product between skin and clothing, watches, shoes, etc.
In the event of an allergic reaction, seek medical attention.
If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

Do not give the patient anything orally.
In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.
Seek medical attention immediately, showing the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Information for the doctor :**

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to remain under medical supervision for 48 hours.
Contact a specialist for treatment poisoning if large quantities have been ingested or inhaled.

## SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

### 5.1. Extinguishing media

**Suitable methods of extinction**

In the event of a fire, use :
- sprayed water or water mist
- foam

**Unsuitable methods of extinction**

In the event of a fire, do not use :
- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.
Do not breathe in smoke.
In the event of a fire, the following may be formed :
- carbon monoxide (CO)
- carbon dioxide (CO2)
- nitrogen oxide (NO)
- nitrogen dioxide (NO2)

**5.3. Advice for firefighters**

Firefighters should wear suitable protective clothing and a respirator mask with self- full operated in positive pressure mode.
Wear conform with the European standard EN 469.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid any contact with the skin and eyes.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.
Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Neutralise with an acidic decontaminant.
If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.
Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.
Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.
Avoid exposure to pregnant women and warn women of child-bearing age of the possible risks

**7.1. Precautions for safe handling**

Always wash hands after handling.
Remove and wash contaminated clothing before re-using.
Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

**Fire prevention :**

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.
Observe precautions stated on label and also industrial safety regulations.
Avoid exposure - obtain special instructions before use.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Store in original container protected from direct sunlight in a dry, cool and well ventilated area away from heat sources.
Keep container tightly closed in a dry place.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

Scope advised: Stratification

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

**8.1. Control parameters**

**Occupational exposure limits :**

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

| CAS | VME-mg/m3 : | VME-ppm : | VLE-mg/m3 : | VLE-ppm : | Notes : |
|---|---|---|---|---|---|
| 80-05-7 | 2 | - | - | - | - |

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

| CAS | VME : | VME : | Excess | Notes |
|---|---|---|---|---|
| 80-05-7 | | 5 mg/m³ | | 1(Î™) |
| 100-51-6 | | 5 ppm<br>22 mg/m³ | | 2 (I) |

- France (INRS - ED984 / 2019-1487) :

| CAS | VME-ppm : | VME-mg/m3 : | VLE-ppm : | VLE-mg/m3 : | Notes : | TMP No : |
|---|---|---|---|---|---|---|
| 80-05-7 | | 2 | - | - | R1B | |

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

| CAS | TWA : | STEL : | Ceiling : | Definition : | Criteria : |
|---|---|---|---|---|---|
| 80-05-7 | - ppm<br>10 mg/m³ | - ppm<br>- mg/m³ | | | |

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

BENZYL ALCOHOL (CAS: 100-51-6)

| **Final use:** | **Workers.** |
|---|---|
| Exposure method: | Dermal contact. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 40 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 8 mg/kg de poids corporel/jour |
| Exposure method: | Inhalation. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 110 mg de substance/m3 |
| Exposure method: | Inhalation. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 22 mg de substance/m3 |

| **Final use:** | **Consumers.** |
|---|---|
| Exposure method: | Ingestion. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 4 mg/kg de poids corporel/jour |
| Exposure method: | Ingestion. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 20 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 4 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 20 mg/kg de poids corporel/jour |
| Exposure method: | Inhalation. |
| Potential health effects: | Long term systemic effects. |

| | |
|---|---|
| DNEL : | 5.4 mg de substance/m3 |
| Exposure method: | Inhalation. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 27 mg de substance/m3 |

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

| | |
|---|---|
| **Final use:** | **Workers.** |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 0.91 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term local effects. |
| DNEL : | 0.044 mg de substance/cm2 |
| Exposure method: | Inhalation. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 8550 mg de substance/m3 |
| Exposure method: | Inhalation. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 1.59 mg de substance/m3 |
| **Final use:** | **Consumers.** |
| Exposure method: | Ingestion. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 32 mg/kg de poids corporel/jour |
| Exposure method: | Ingestion. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 0.65 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 13 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Short term local effects. |
| DNEL : | 1.59 mg de substance/cm2 |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 0.4 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term local effects. |
| DNEL : | 0.68 mg de substance/cm2 |
| Exposure method: | Inhalation. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 2542 mg de substance/m3 |
| Exposure method: | Inhalation. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 0.46 mg de substance/m3 |

BISPHENOL A (CAS: 80-05-7)

| | |
|---|---|
| **Final use:** | **Workers.** |
| Exposure method: | Dermal contact. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 0.031 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |

Potential health effects: Long term systemic effects.
DNEL : 0.031 mg/kg de poids corporel/jour

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 2 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 2 mg de substance/m3

**Final use:** **Man exposed via the environment.**
Exposure method: Ingestion.
Potential health effects: Short term systemic effects.
DNEL : 0.004 mg/kg de poids corporel/jour

Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 0.004 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Short term systemic effects.
DNEL : 0.002 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.002 mg/kg de poids corporel/jour

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 1 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 1 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 1 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Short term local effects.
DNEL : 1 mg de substance/m3

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

**Final use:** **Workers.**
Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.91 mg/kg de poids corporel/jour

Exposure method: Dermal contact.
Potential health effects: Long term local effects.
DNEL : 0.44 mg de substance/cm2

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 8550 mg de substance/m3

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 1.59 mg de substance/m3

**Final use:** **Consumers.**
Exposure method: Ingestion.

| | |
|---|---|
| Potential health effects: | Short term systemic effects. |
| DNEL : | 32 mg/kg de poids corporel/jour |
| Exposure method: | Ingestion. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 0.65 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 13 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Short term local effects. |
| DNEL : | 1.59 mg de substance/cm2 |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 0.4 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term local effects. |
| DNEL : | 0.68 mg de substance/cm2 |
| Exposure method: | Inhalation. |
| Potential health effects: | Short term systemic effects. |
| DNEL : | 2542 mg de substance/m3 |
| Exposure method: | Inhalation. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 0.46 mg de substance/m3 |

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

| | |
|---|---|
| **Final use:** | **Workers.** |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 2.5 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term local effects. |
| DNEL : | 0.623 mg de substance/cm2 |
| **Final use:** | **Consumers.** |
| Exposure method: | Ingestion. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 0.04 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term systemic effects. |
| DNEL : | 1.25 mg/kg de poids corporel/jour |
| Exposure method: | Dermal contact. |
| Potential health effects: | Long term local effects. |
| DNEL : | 0.311 mg de substance/cm2 |

**Predicted no effect concentration (PNEC):**

BENZYL ALCOHOL (CAS: 100-51-6)

| | |
|---|---|
| Environmental compartment: | Soil. |
| PNEC : | 0.456 mg/kg |
| Environmental compartment: | Fresh water. |
| PNEC : | 1 mg/l |
| Environmental compartment: | Sea water. |

| | |
|---|---|
| PNEC : | 0.1 mg/l |
| Environmental compartment: | Intermittent waste water. |
| PNEC : | 2.3 mg/l |
| Environmental compartment: | Fresh water sediment. |
| PNEC : | 5.27 mg/kg |
| Environmental compartment: | Marine sediment. |
| PNEC : | 0.527 mg/kg |
| Environmental compartment: | Waste water treatment plant. |
| PNEC : | 39 mg/l |

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

| | |
|---|---|
| Environmental compartment: | Soil. |
| PNEC : | 0.18 mg/kg |
| Environmental compartment: | Fresh water. |
| PNEC : | 2.5 µg/l |
| Environmental compartment: | Sea water. |
| PNEC : | 2.5 µg/l |
| Environmental compartment: | Fresh water sediment. |
| PNEC : | 0.22 mg/kg |
| Environmental compartment: | Marine sediment. |
| PNEC : | 0.14 mg/kg |
| Environmental compartment: | Waste water treatment plant. |
| PNEC : | 1.64 mg/l |

BISPHENOL A (CAS: 80-05-7)

| | |
|---|---|
| Environmental compartment: | Soil. |
| PNEC : | 3.7 mg/kg |
| Environmental compartment: | Fresh water. |
| PNEC : | 0.018 mg/l |
| Environmental compartment: | Sea water. |
| PNEC : | 0.018 mg/l |
| Environmental compartment: | Fresh water sediment. |
| PNEC : | 1.2 mg/kg |
| Environmental compartment: | Marine sediment. |
| PNEC : | 0.24 mg/kg |
| Environmental compartment: | Waste water treatment plant. |
| PNEC : | 320 mg/l |

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

| | |
|---|---|
| Environmental compartment: | Soil. |
| PNEC : | 10 mg/kg |
| Environmental compartment: | Fresh water. |
| PNEC : | 1.6 µg/l |
| Environmental compartment: | Sea water. |
| PNEC : | 1.6 µg/l |
| Environmental compartment: | Fresh water sediment. |
| PNEC : | 0.14 mg/kg |

| | |
|---|---|
| Environmental compartment: | Marine sediment. |
| PNEC : | 0.14 mg/kg |
| Environmental compartment: | Waste water treatment plant. |
| PNEC : | 3.19 mg/l |

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

| | |
|---|---|
| Environmental compartment: | Soil. |
| PNEC : | 0.0176 mg/kg |
| Environmental compartment: | Fresh water. |
| PNEC : | 0.015 mg/l |
| Environmental compartment: | Sea water. |
| PNEC : | 0.0143 mg/l |
| Environmental compartment: | Intermittent waste water. |
| PNEC : | 0.15 mg/l |
| Environmental compartment: | Fresh water sediment. |
| PNEC : | 0.132 mg/kg |
| Environmental compartment: | Marine sediment. |
| PNEC : | 0.125 mg/kg |
| Environmental compartment: | Waste water treatment plant. |
| PNEC : | 7.5 mg/l |

**8.2. Exposure controls**

Use only with adequate ventilation or provided with ventilation at the source.

**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :

Use personal protective equipment that is clean and has been properly maintained.
Store personal protective equipment in a clean place, away from the work area.
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.
Use eye protectors designed to protect against liquid splashes
Before handling, wear safety goggles with protective sides accordance with standard EN166.
In the event of high danger, protect the face with a face shield.
Prescription glasses are not considered as protection.
Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.
Provide eyewash stations in facilities where the product is handled constantly.

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.
Gloves must be selected according to the application and duration of use at the workstation.
Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.
Type of gloves recommended :
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- Butyl Rubber (Isobutylene-isoprene copolymer)
Recommended properties :
- Impervious gloves in accordance with standard EN374

**- Body protection**

Avoid skin contact.
Wear suitable protective clothing.

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.
In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.
Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.
Work clothing worn by personnel shall be laundered regularly.
After contact with the product, all parts of the body that have been soiled must be washed.

**- Respiratory protection**

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :
Mask with filter type A, B, E, K, P
Attention! If the protection group is insufficient.

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

**General information :**

| | |
|---|---|
| Physical state : | Fluid liquid. |
| Color: | yellow |

**Important health, safety and environmental information**

| | |
|---|---|
| pH : | Not stated. |
| | Slightly basic. |
| Boiling point/boiling range : | Not relevant. |
| Flash Point Interval : | FP > 100°C. |
| Vapour pressure (50°C) : | Not relevant. |
| Density : | 1.02 ± 0.02 @ 20 °C |
| Water solubility : | Soluble. |
| Viscosity : | 280 ± 50 mPa.s @ 25°C |
| Melting point/melting range : | Not relevant. |
| Self-ignition temperature : | Not relevant. |
| Decomposition point/decomposition range : | Not relevant. |
| Index of refraction : | 1.5020 ± 0.002 @ 25 °C |
| % VOC : | 0 |

### 9.2. Other information

| | |
|---|---|
| Miscibility | Alcohols, aromatic solvents |

## SECTION 10 : STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

No data available.

### 10.5. Incompatible materials

Keep away from :
- strong oxidising agents

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO2)
- nitrogen oxide (NO)
- nitrogen dioxide (NO2)

## SECTION 11 : TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure between three minutes and one hour.
Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of

the skin, complete areas of alopecia, and scars.
May cause an allergic reaction by skin contact.
Presumed human reproductive toxicant.
May damage fertility and suspected of damaging the unborn child.

**11.1.1. Substances**

**Acute toxicity :**

SALICYLIC ACID (CAS: 69-72-7)

| | |
|---|---|
| Oral route : | LD50 = 891 mg/kg<br>Species : Rat<br>OCDE Ligne directrice 401 (Toxicité aiguë par voie orale) |

BENZYL ALCOHOL (CAS: 100-51-6)

| | |
|---|---|
| Oral route : | LD50 = 1620 mg/kg<br>Species : Rat |
| Dermal route : | LD50 = 2000 mg/kg<br>Species : Rat |
| Inhalation route (Dusts/mist) : | LC50 = 5 mg/l<br>Species : Rat<br>OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)<br>Duration of exposure : 4 h |

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

| | |
|---|---|
| Oral route : | LD50 = 1600 mg/kg<br>Species : Rat |
| Dermal route : | LD50 = 1465.4 mg/kg<br>Species : Rabbit<br>OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée) |

BISPHENOL A (CAS: 80-05-7)

| | |
|---|---|
| Oral route : | LD50 = 3250 mg/kg<br>Species : Rat |
| Dermal route : | LD50 = 3000 mg/kg<br>Species : Rabbit |

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

| | |
|---|---|
| Oral route : | LD50 = 1716.2 mg/kg<br>Species : Rat<br>OCDE Ligne directrice 401 (Toxicité aiguë par voie orale) |
| Dermal route : | LD50 = 1465.4 mg/kg<br>Species : Rabbit<br>OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée) |

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

| | |
|---|---|
| Oral route : | LD50 = 2885.3 mg/kg<br>Species : Rat |
| Dermal route : | LD50 = 2979.7 mg/kg<br>Species : Rabbit |

**Skin corrosion/skin irritation :**

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

| | |
|---|---|
| Corrosivity : | Causes severe skin burns.<br>Species : Rabbit<br>OCDE Ligne directrice 404 (Effet irritant/corrosif aigu sur la peau.) |

**Respiratory or skin sensitisation :**

BENZYL ALCOHOL (CAS: 100-51-6)

| | |
|---|---|
| Guinea Pig Maximisation Test (GMPT) : | Non-sensitiser. |

Species : Guinea pig
OCDE Ligne directrice 406 (Sensibilisation de la peau)

BISPHENOL A (CAS: 80-05-7)

Species : Guinea pig

**Germ cell mutagenicity :**

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

No mutagenic effect.

Mutagenesis (in vivo) : Negative.

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

No mutagenic effect.

Mutagenesis (in vivo) : Negative.
OCDE Ligne directrice 474 (Le test de micronoyaux sur les érythrocytes de mammifères)

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

No mutagenic effect.

**Carcinogenicity :**

BENZYL ALCOHOL (CAS: 100-51-6)

Carcinogenicity Test : Negative.
No carcinogenic effect.
Species : Mouse
OCDE Ligne directrice 453 (Études combinées de toxicité chronique et de cancérogénèse)

**Reproductive toxicant :**

BISPHENOL A (CAS: 80-05-7)
May damage fertility.

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

OCDE Ligne directrice 414 (Étude de la toxicité pour le développement prénatal)

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)
No toxic effect for reproduction

Study on development : Species : Rat
OCDE Ligne directrice 421 (Essai de dépistage de la toxicité pour la reproduction et le développement)

**Specific target organ systemic toxicity - repeated exposure :**

BENZYL ALCOHOL (CAS: 100-51-6)

Oral route : C = 400 mg/kg poids corporel/jour
Species : Rat
Duration of exposure : 90 jours

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Species : Rat

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

Oral route : C = 239 mg/kg poids corporel/jour
Species : Rat
Duration of exposure : 28 jours
OCDE Ligne directrice 407 (Toxicité orale à doses répétées - pendant 28 jours sur les rongeurs)

Dermal route : C = 250 mg/kg poids corporel/jour
Duration of exposure : 90 jours
OCDE Ligne directrice 411 (Toxicité cutanée subchronique: 90 jours)

**11.1.2. Mixture**

No toxicological data available for the mixture.

## SECTION 12 : ECOLOGICAL INFORMATION

Very toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

**12.1. Toxicity**

**12.1.1. Substances**

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

| | |
|---|---|
| Fish toxicity : | Duration of exposure : 96 h |
| Crustacean toxicity : | Duration of exposure : 48 h<br><br>NOEC = 0.8 mg/l<br>Species : Daphnia magna<br>Duration of exposure : 21 jours |
| Algae toxicity : | ECr50 = 0.7 mg/l<br>Factor M = 1<br>Species : Pseudokirchnerella subcapitata<br>Duration of exposure : 72 h<br>OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)<br><br>NOEC = 0.25 mg/l<br>Duration of exposure : 72 h |

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

| | |
|---|---|
| Fish toxicity : | LC50 > 15 mg/l<br>Species : Others<br>Duration of exposure : 96 h<br>OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë) |
| Crustacean toxicity : | EC50 = 80 mg/l<br>Species : Others<br>Duration of exposure : 48 h<br>OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate) |

BENZYL ALCOHOL (CAS: 100-51-6)

| | |
|---|---|
| Fish toxicity : | LC50 = 460 mg/l<br>Species : Pimephales promelas<br>Duration of exposure : 96 h<br>OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë) |
| Crustacean toxicity : | EC50 = 230 mg/l<br>Species : Daphnia magna<br>Duration of exposure : 48 h<br>OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)<br><br>NOEC = 51 mg/l<br>Species : Daphnia magna<br>Duration of exposure : 21 jours<br>OCDE Ligne directrice 211 (Daphnia magna, essai de reproduction) |
| Algae toxicity : | ECr50 = 770 mg/l<br>Duration of exposure : 72 h<br>OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)<br><br>NOEC = 310 mg/l<br>Duration of exposure : 72 h<br>OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance) |

BISPHENOL A (CAS: 80-05-7)

| | |
|---|---|
| Fish toxicity : | LC50 = 4.6 mg/l<br>Species : Pimephales promelas<br>Duration of exposure : 96 h<br><br>NOEC = 0.016 mg/l<br>Species : Others |
| Crustacean toxicity : | EC50 = 7.75 mg/l<br>Species : Others<br>Duration of exposure : 48 h<br><br>NOEC = 1.8 mg/l |
| Algae toxicity : | ECr50 = 2.73 mg/l<br>Species : Pseudokirchnerella subcapitata<br>Duration of exposure : 96 h |

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

| | |
|---|---|
| Fish toxicity : | LC50 = 100 mg/l<br>Species : Poecilia reticulata<br>Duration of exposure : 96 h |
| Crustacean toxicity : | EC50 = 2.2 mg/l<br>Species : Daphnia magna<br>Duration of exposure : 48 h |
| Algae toxicity : | ECr50 = 0.23 mg/l<br>Species : Pseudokirchnerella subcapitata<br>Duration of exposure : 72 h |

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

**12.2.1. Substances**

BENZYL ALCOHOL (CAS: 100-51-6)

Biodegradability : Rapidly degradable.

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

BISPHENOL A (CAS: 80-05-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Biodegradability : Non-rapidly degradable.

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

**12.3. Bioaccumulative potential**

**12.3.1. Substances**

BENZYL ALCOHOL (CAS: 100-51-6)

Octanol/water partition coefficient : log Koe = 1.1

BISPHENOL A (CAS: 80-05-7)

Octanol/water partition coefficient : log Koe = 3.3

Bioaccumulation : BCF = 73

Made under licence of European Label System, Software of INFODYNE (http://www.infodyne.fr)

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)
Octanol/water partition coefficient : log Koe = -3.67

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)
Octanol/water partition coefficient : log Koe = 1.34

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 3 : Extremely hazardous for water.

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.
Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.
Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.
Give to a certified disposal contractor.

**Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :**

07 01 08 * other still bottoms and reaction residues

## SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2020).

**14.1. UN number**

2735

**14.2. UN proper shipping name**

UN2735=AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(reaction products of di-, tri and tetra-propoxylated propane-1.2-diol with ammonia, polyethylenepolyamines)

**14.3. Transport hazard class(es)**

- Classification :

8

**14.4. Packing group**

III

**14.5. Environmental hazards**

- Environmentally hazardous material :

**14.6. Special precautions for user**

| ADR/RID | Class | Code | Pack gr. | Label | Ident. | LQ | Provis. | EQ | Cat. | Tunnel |
|---|---|---|---|---|---|---|---|---|---|---|
| | 8 | C7 | III | 8 | 80 | 5 L | 274 | E1 | 3 | E |
| IMDG | Class | 2°Label | Pack gr. | LQ | EMS | Provis. | EQ | Stowage Handling | Segregation | |
| | 8 | - | III | 5 L | F-A, S-B | 223 274 | E1 | Category A | SGG18 SG35 | |
| IATA | Class | 2°Label | Pack gr. | Passager | Passager | Cargo | Cargo | note | EQ | |
| | 8 | - | III | 852 | 5 L | 856 | 60 L | A3 A803 | E1 | |
| | 8 | - | III | Y841 | 1 L | - | - | A3 A803 | E1 | |

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.
For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

## SECTION 15 : REGULATORY INFORMATION

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)

**- Container information:**

No data available.

**Usage restrictions apply to the product : See annex XVII of EC regulation No. 1907/2006.**

For professional users only.

**- Particular provisions :**

No data available.

**- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 3 : Extremely hazardous for water.

**- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :**

NFPA 704, Labelling: Health=3 Inflammability=1 Instability/Reactivity=1 Specific Risk=none




**15.2. Chemical safety assessment**

No data available.

## SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.
The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.
It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.
The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

| | |
|---|---|
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |

| | |
|---|---|
| H335 | May cause respiratory irritation. |
| H360F | May damage fertility. |
| H361d | Suspected of damaging the unborn child. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

**Abbreviations :**

DNEL : Derived No-Effect Level
PNEC : Predicted No-Effect Concentration
CMR: Carcinogenic, mutagenic or reprotoxic.
UFI : Unique Formula Identifier
ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
WGK : Wassergefahrdungsklasse (Water Hazard Class).
GHS05 : Corrosion
GHS07 : Exclamation mark
GHS08 : Health hazard
GHS09 : Environment
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
SVHC : Substances of very high concern.

Made under licence of European Label System, Software of INFODYNE (http://www.infodyne.fr)