

LTS90B/LTS90G

Vacuum Bag Sealant Tape

- Economic low cost vacuum bag sealant tape
- Excellent tack
- Ideally suited to debulking operations at ambient temperatures and high temperature envelope bagging applications
- Material compatible with most substrates (including composite tools) and film materials
- For optimum results, tape must be allowed to cool to ambient before stripping from mould surfaces

PHYSICAL PROPERTIES

- Maximum Use Temperature Up to 150°C bag to tool
Up to 180°C bag to bag
- Colour Black (LTS90B), Grey (LTS90G)
- Solids 100%
- Flammability Not flammable but combustible

AVAILABILITY & PACKAGING

- Roll size 15m x 12mm x 3mm
(also available as a 4mm diameter bead)
- Standard box contents 22 rolls

STORAGE & HANDLING

- LTS90 has low toxicity, is non irritant and non injurious to skin
- It should be stored in its original containers, under ideal conditions of between 5 and 25°C
- The material has a 1 year shelf life
- Material must be stored flat

suter-kunststoffe ag
swiss-composite.ch

CH-3312 Fraubrunnen 031 763 60 60 Fax 031 763 60 61
www.swiss-composite.ch info@swiss-composite.ch

Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: sales@aerovac.com website: www.aerovac.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.