

ISOTACKER Adhesive Epoxy Spray

Epoxy fixative spray formulated for dry layup, fixing, positioning and preforming fabric (carbon, aramid, linen etc. ...).

Formulation 100% epoxy compatible, miscible, invisible in the resin and the composite after lamination, infusion or injection.

Compatibility with other resin systems (PU, polyester, vinylester, etc. ...), please contact us.

NOTE: Make sure of the compatibility of finishes, surface treatment of fabrics and mold release waxes before use.

The perfect compatibility of the fastening system with the majority of epoxy resins do not exclude reasonable use of this spray, an excess of product may affect the final performance of the composite.

Application

Shake well before use. The surfaces that need to be fixed must be perfectly clean and dry.

Hold the spray can at the vertical and spray a thin coat evenly on the surface.

Hold the can 20cm away from the fabric

You must obtain a « non wet » aspect if not then hold the spray can further away from your working surface.

To obtain a better fixing quality, spray both side that need to be glued

Wait 1 minute then push together both sprayed surfaces until the adhesive has taken

After every use, bleed the spray head down

Temperature: optimum temperature 15-30°C

Packaging: 500ml can



LEGAL NOTES: SICOMIN reserves the right to change the properties of its products. All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data and tolerance may vary due to circumstances beyond our control. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.

MENTIONS LÉGALES : SICOMIN se réserve le droit de modifier les propriétés du produit. Toutes les caractéristiques spécifiées dans cette Fiche technique sont basées sur des tests de laboratoire. Les mesures et leurs tolérances effectives peuvent varier pour différentes raisons. SICOMIN ne donne aucune garantie de quelque nature que ce soit si ce n'est que les matériaux fournis sont de qualité standard. Tous les risques et responsabilités découlant de la manutention, le stockage et l'utilisation des produits, ainsi que le respect des restrictions légales applicables, incombe à l'utilisateur.